



PRODUCT PROFILE

GENERAL PRODUCT SPECIFICATIONS

Article: **INCA NABUK**
Compositon: 88% PVC 8%PES 4%COT

Width: 140 cm+/-2cm
Weight: 600gr/m²

Suitable for

√ Upholstery
√ Light upholstery

√ Contract
√ Bed covering

Care codes

INCA NABUK
surface washable with water and
Washable: neutral soap

Test Specifications

Tensile resistance:
Ultimate elongation:
Tear resistance:
Peel adhesion:
Bally 23°C
Bally -10°C
Xeno test
Tropical test - jungle test (70° -95% humidity)
Martindales:
Flame retardant norms
Light fastness:

INCA NABUK

UNI EN ISO 1421 300 minimum
UNI EN ISO 1421 160 minimum
UNI EN ISO 4674 meth.B 25minimum
UNI 4818 P.10 30minimum
UNI 4818 P.13 150.000 cycles
UNI 4818 P.13
UNI ISO 4582/4892 blue scale 7 minimum
UNI EN ISO 1419/C - 1995 E RESISTANSE
UNI EN ISO 12947-2-200 102.400 cycles
UNI 9175 - CLASSE 1 IM ISO 3795 BS 5852 FMVSS 302
7

INCA NABUK

Made in: Italy



